

**WEST**[Help](#)[Logout](#)[Main Menu](#) [Search Form](#) [Result Set](#) [Show S Numbers](#) [Edit S Numbers](#) [Referring Patents](#)[First Hit](#)[Previous Document](#)[Next Document](#)[Full](#)[Title](#)[Citation](#)[Front](#)[Review](#)[Classification](#)[Date](#)[Reference](#)[Claims](#)[KWIC](#)**Document Number 1**

Entry 1 of 6

File: USPT

Oct 5, 1999

DOCUMENT-IDENTIFIER: US 5963625 A

TITLE: Method for providing called service provider control of caller access to pay services

**DEPR:**

The limiting or restricting effects of the sponsors' ANI blocking table may be overridden by the caller's providing account plus PIN or other identification data when ANI is unavailable or determined to be invalid or by achieving a high caller score as further described below.

[Main Menu](#) [Search Form](#) [Result Set](#) [Show S Numbers](#) [Edit S Numbers](#) [Referring Patents](#)[First Hit](#)[Previous Document](#)[Next Document](#)[Full](#)[Title](#)[Citation](#)[Front](#)[Review](#)[Classification](#)[Date](#)[Reference](#)[Claims](#)[KWIC](#)[Help](#)[Logout](#)

**WEST**[Help](#)[Logout](#)[Main Menu](#) [Search Form](#) [Result Set](#) [Show S Numbers](#) [Edit S Numbers](#) [Referring Patents](#)[First Hit](#)[Previous Document](#)[Next Document](#)[Full](#)[Title](#)[Citation](#)[Front](#)[Review](#)[Classification](#)[Date](#)[Reference](#)[Claims](#)[KWIC](#)**Document Number 3**

Entry 3 of 6

File: USPT

Aug 18, 1998

DOCUMENT-IDENTIFIER: US 5796810 A

TITLE: Apparatus for dialing of caller ID block code and receiving call waiting caller-ID-signal

**ABPL:**

An apparatus for providing a convenient and flexible way for a user to dial a block code which allows the user to withhold his/her identity and telephone number when the user makes a phone call. By programming different operation modes using the keys when the apparatus is in an on-hook status, the user may elect to have a block code dialed by manually pressing a block key when desired, or to have a prompt message displayed on the screen to remind him/her to press a key to dial the block code, if so desired, when the phone is off-hook, or to have the block code auto-dialed every time the phone is off-hook. When the apparatus is in an automatic block code dialing mode, the user may override this setting and have his/her caller ID sent on a per call basis. Another aspect of the invention is a circuit arrangement which is capable of reducing the speech/voice interference to the call waiting caller-ID-alert signal during normal telephone conversation, thus improving the chance of a successful caller ID data transmission during call waiting.

[Main Menu](#) [Search Form](#) [Result Set](#) [Show S Numbers](#) [Edit S Numbers](#) [Referring Patents](#)[First Hit](#)[Previous Document](#)[Next Document](#)[Full](#)[Title](#)[Citation](#)[Front](#)[Review](#)[Classification](#)[Date](#)[Reference](#)[Claims](#)[KWIC](#)[Help](#)[Logout](#)